



Steering, Brake & Suspension Specialists

#6467RTUL-K & #6872RTUL-K- Installation Instructions for 1964-72 GM "A" Body 4-Link

Parts:

1 ea	Left Lower Control Arm Assembly
1 ea	Right Lower Control Arm Assembly
2 ea	Upper Control Arm Assemblies
4 ea	Lock-Out Plates
8 ea	1/2-13x4 gr. 8 Bolts
8 ea	1/2 Lock Washers
16 ea	1/2 Flat Washers

- Remove the original lower links.
- Install the new lower links. The anti-roll bar mounting tabs should be down, reward and inboard. If the anti-roll bar is being used install it now.
- Install the coil springs.

Instructions:

- Remove the coil springs.
- Remove the original upper links.
- Install the new upper links and lockout plates.



Lock Out Plate



Anti-Roll Bar Mount

GENERAL TORQUE SPECIFICATIONS:

1/4"	grade 5	10lb/ft	1/4"	grade 8	14lb/ft
5/16"	grade 5	19lb/ft	5/16"	grade 8	29lb/ft
3/8"	grade 5	33lb/ft	3/8"	grade 8	47lb/ft
7/16"	grade 5	54lb/ft	7/16"	grade 8	78lb/ft
1/2"	grade 5	78lb/ft	1/2"	grade 8	119lb/ft
9/16"	grade 5	114lb/ft	9/16"	grade 8	169lb/ft
5/8"	grade 5	154lb/ft	5/8"	grade 8	230lb/ft

For technical help call Classic Performance Products Monday thru Friday 8:30am to 5:00pm at (714) 522-2000.

Classic Performance Products, Inc. 714.522.2000 | fax 714.522.2500

378 E. Orangethorpe Ave. | Placentia, CA 92870 | www.classicperform.com